


SINGLE-SEAL EXPANSION JOINT

Wall to Wall | Corner Wall


25 - 100 mm (1 - 4") Expansion Gaps

MaxAtec 140 : A07-A09

MaxAtec 140 : A07



MaxAtec 140 : A09



Expansion Joint Selection Criteria

Load Rating

Product Details

Joint Location	Gap Width B(mm)	Movement Capacity (mm)		Eurocode Rating				Product Dimensions		Sightline A (mm)	Blockout C (mm)	Product Number
		±	[Total]					H1 (mm)	H2 (mm)			
Wall - Wall	25	± 6	[12]	-	-	-	-	18	-	70	200	140-A07-025
	50	± 12	[25]							87	217	140-A07-050
	75	± 20	[40]							111	241	140-A07-075
	100	± 25	[50]							136	266	140-A07-100
Corner Wall	25	± 6	[12]	-	-	-	-	18	58	70	136	140-A09-025
	50	± 12	[25]							86	152	140-A09-050
	75	± 20	[40]							111	176	140-A09-075
	100	± 25	[50]							136	201	140-A09-100

Features

Surface

Ribbed surface for greater movement

Movement

High movement capacity

ASTM E-1399 Class I: Thermal

Class II: Wind

Traffic Frequency per day



- - - - -

System Options

Gap width(s)	25, 50, 75, 100 mm
Height(s)	18 mm
Metal type(s)	Aluminium
Seal colour(s)	Black, Grey, Stone
Fire barrier	120-240 minutes
Waterproofing	Moisture barrier
Pre-assembly in factory	Contact Vexcolt



MaxAtec 140 : A07-A09

APPLICATIONS

Airport Terminals | Educational | Exhibition Centres
Department Stores | Distribution & Retail Warehouses
Factories | Hospitals | Museums | Offices & Hotels
Parking | Places of Worship | Residential Buildings
Rail, Metros & Elevated Rail Stations | Roads & Bridges
Shopping Centres | Sports Stadiums | Supermarkets