


SINGLE-SEAL EXPANSION JOINT

Wall to Wall | Corner to Wall


25 - 50 mm (1 - 2") Expansion Gaps

MaxAtec 130 : A07-A09

MaxAtec 130 : A07



MaxAtec 130 : A09



Expansion Joint Selection Criteria

Load Rating

Product Details

Joint Location	Gap Width B (mm)	Movement Capacity (mm)		Eurocode Rating				Product Dimensions				Product Number
		±	[Total]					Height		Sight-A	Blockout C	
				H1 (mm)	H2 (mm)	A (mm)	C (mm)					
Wall - Wall	25	± 5	[10]	-	-	-	-	10: 15	-	25	125	130-A07-025-(H1)
	50	± 10	[20]	-	-	-	-	10: 15	-	48	147	130-A07-050-(H1)
Corner - Wall	25	± 5	[10]	-	-	-	-	10: 15	45	25	75	130-A09-025-(H1)
	50	± 10	[20]	-	-	-	-	10: 15	45	48	97	130-A09-050-(H1)

When specifying or ordering please add the **height (H1)** required to the Product Reference.
For example MaxAtec 130 : A07-025-010 denotes a joint 10 mm high.

Features

Surface

Smooth surface

Movement

Good movement capacity

ASTM E-1399 Class I: Thermal

Class II: Wind

Traffic Frequency per day



- - - - -

System Options

Gap width(s)	25, 50 mm
Height(s)	10, 15 mm
Metal type(s)	6063 T5 & T6 Aluminium
Seal colour(s)	Black (RAL 7021) Grey (RAL 7038) Beige (RAL 1015)
Fire barrier	120 minutes
Waterproofing	Moisture barrier
Pre-assembly in factory	Contact Vexcolt

MaxAtec 130 : A07-A09



APPLICATIONS

Airport Terminals | Educational | Exhibition Centres
 Department Stores | Distribution & Retail Warehouses
 Factories | Hospitals | Museums | Offices & Hotels
 Parking | Places of Worship | Residential Buildings
 Rail, Metros & Elevated Rail Stations | Roads & Bridges
 Shopping Centres | Sports Stadiums | Supermarkets