

# **MegAtec 300 :** A01-A02

# MegAtec 300 : A01



# MegAtec 300: A02



# Expansion Joint Selection Criteria Load Rating Product Details

Expansion some selection enteria			Louis Mating				1 Toddet Betails					
Joint Gap Mo		Movemen	Movement		Eurocode Rating			Product Dimensions			Product	
Location	Width	Capacity (mm)						Hei	Height		Blockout	Number
	B (mm)	±	[Total]				00 0	H1 (mm)	H2 (mm)	A (mm)	C (mm)	
Floor - Floor	25	± 5	[10]	10 kN	69 kN	30 kN	300kN	25: 35: 50: 75: 100	-	69	185	300-A01-025-(H1)
	50	± 10	[20]							94	210	300-A01-050-(H1)
	75	± 15	[30]							119	235	300-A01-075-(H1)
	100	± 20	[40]							144	260	300-A01-100-(H1)
	125	± 30	[60]							169	285	300-A01-125-(H1)
	150	± 40	[80]							194	310	300-A01-150-(H1)
Floor - Wall	25	± 5	[10]	10 kN	69 kN	30 kN	300kN	25: 35: 50: 75: 100	70	69	127	300-A02-025-(H1)
	50	± 10	[20]							94	152	300-A02-050-(H1)
	75	± 15	[30]							119	177	300-A02-075-(H1)
	100	± 20	[40]							144	202	300-A02-100-(H1)
	125	± 30	[60]							169	227	300-A02-125-(H1)
	150	± 40	[80]							194	252	300-A02-150-(H1)

When specifying or ordering please add the **height (H1)** required to the Product Reference. For example MegAtec 300: A01-075-050 denotes a joint 50mm high.



Floor to Floor | Floor to Wall 25 - 150 mm (1 - 6") Expansion Gaps

## **Features**

### Surface

Smooth transit

Hairline serrated surface for improved slip resistance Americans with Disabilities Act (ADA) compliant across the entire movement cycle

#### Movement

High movement capacity

ASTM E-1399 Class I: Thermal Class II: Wind

# **Traffic Frequency per day**

À				
> 25,000	≤ 1,000	≤ 1,000	≤ 1,000	≤ 10

# **System Options**

Gap width(s)	25, 50, 75, 100, 125, 150 mm
Height(s)	25, 35, 50, 75, 100 mm
Metal type(s)	6063 T5 & T6 aluminium
Fire barrier	120 minutes
Waterproofing	Moisture barrier
Pre-assembly in factory	Contact Vexcolt

