


SINGLE-SEAL EXPANSION JOINT

Wall to Wall | Corner to Wall


50 - 100 mm (2 - 4") Expansion Gaps

MaxAtec 110 : A07-A09

MaxAtec 110 : A07



MaxAtec 110 : A09



Expansion Joint Selection Criteria

Load Rating

Product Details

Joint Location	Gap Width B(mm)	Movement Capacity (mm)		Eurocode Rating				Product Dimensions				Product Number
		±	[Total]					Height		Sightline	Blockout	
				H1 (mm)	H2 (mm)	A (mm)	C (mm)					
Wall - Wall	50	± 25	[50]	-	-	-	-	55	-	50	50	110-A07-050
	75	± 37	[75]	-	-	-	-	55	-	75	75	110-A07-075
	100	± 50	[100]	-	-	-	-	55	-	100	100	110-A07-100
Corner - Wall	50	± 25	[50]	-	-	-	-	55	55	50	50	110-A09-050
	75	± 37	[75]	-	-	-	-	55	55	75	75	110-A09-075
	100	± 50	[100]	-	-	-	-	55	55	100	100	110-A09-100

Features

Surface

Ribbed surface for improved movement

Movement

Good movement capacity

ASTM E-1399 Class I: Thermal
 Class II: Wind
 Class III: Seismic


Traffic Frequency per day



- - - - -

System Options

Gap width(s)	50, 75, 100 mm
Height(s)	55 mm
Metal type(s)	6063 T5 & T6 Aluminium
Seal colour(s)	Black (RAL 7021) Grey (RAL 7038) Beige (RAL 1015)
Fire barrier	120 minutes
Waterproofing	Moisture Barrier
Aluminium Finish	25 micron clear satin anodised
Pre-assembly in factory	Contact Vexcolt



MaxAtec 110 : A07-A09

APPLICATIONS

Airport Terminals | Educational | Exhibition Centres
 Department Stores | Distribution & Retail Warehouses
 Factories | Hospitals | Museums | Offices & Hotels
 Parking | Places of Worship | Residential Buildings
 Rail, Metros & Elevated Rail Stations | Roads & Bridges
 Shopping Centres | Sports Stadiums | Supermarkets